



ELECTRICAL:

VOLTAGE RATING: DC 3V, 120 mA
 INTER-CONTACT RESISTANCE:
 100mΩ Max. at 1KHz w/LOW DRAINAGE
 (100mA MAX.)
 INSULATION RESISTANCE: 100mΩ Min. at 500VDC
 VOLTAGE DURABILITY: 600VDC FOR 1 MIN.

CONTACTS:

NEGATIVE CONTACT: BRASS, NICKEL PLATED
 POSITIVE CONTACT: PHOSPHOR BRONZE, NICKEL PLATED

MATERIAL:

HOUSING: NYLON

MECHANICAL:

INSERTION FORCE: 0.3Kg~1.0Kg
 SPRING PRESSURE: 50G Min.
 TERMINAL STRENGTH: ELECTRICAL AND MECHANICAL PERFORMANCE SPECIFICATIONS SHOULD STILL BE SATISFIED WITHOUT TERMINAL CRACKING OR EXCESSIVE PLAY, WITH A STATIC LOAD OF 1Kg APPLIED TO THE TERMINALS IN ANY DIRECTION. HOWEVER THE TERMINAL MAY BEND

HOW TO ORDER:

B **H** **0** **0** - **1** **1** **0** **0** - **0** **0** **0** - **Z**

STYLE: 1 - Horizontal Thru Hole Flex Housing
BATTERY DIAMETER: 1 - 20mm
PACKAGING: 0 - Tray

RoHS COMPLIANT

Rev	Drawn	Checked	Approved	Date
0	A.M.	S.M.	S.M.	09/11/03
A	MDH	S.M.	S.M.	07/13/04
B	B.S.	S.M.	S.M.	11/29/06

SMP TECHNOLOGY, INC.

Battery Holder, Horizontal, Thru Hole, P.C. Mount For 20.0mm Diameter Battery, Rigid Bottom

SCALE:n/a

TOL. DEC. .X +/- 0.2 .XX +/- .XXX +/- ANGLE +/- UNIT: mm

p/n: BH00-1100-000-Z