



ELECTRICAL:

CURRENT RATING: 1.5A @ 250VAC Min.
 CONTACT RESISTANCE: Before life test: 30m ohm max.
 After life test: 50m ohm max.
 INSULATION RESISTANCE: 1000 M ohm min.
 DIELECTRIC WITHSTANDING VOLTAGE:
 750V (rms) AC for 1 Minute
 CAPACITANCE: 2pF Max.

MATERIAL:

INSULATOR: Thermoplastic UL94V-0
 CONTACTS: Material: Phosphor Bronze t:0.25mm
 CONTACT PLATING: Gold/Tin Plating
 SHELL: Brass t:0.3mm
 SHELL PLATING: Tin or Nickel Plated

HOW TO ORDER:

U 0 0 1 - 1 2 0 0 - 2 0 X - Z

NUMBER OF CONTACTS: 12 - 12 Pin Triple Port

INSULATOR COLOR: 0 - Black

NUMBER OF LOCKS: 0 - Standard 2 Locks (Top, Bottom, Sides)

RoHS COMPLIANT

DEFINITION: 0 - Right Angle, Thru Hole

SHELL STYLE: 2 - 2 Front Springs

SELECTIVE CONTACT PLATING:
 1 - Gold
 3 - 15µ" AuGold
 4 - 30µ" AuGold

Rev					Apv.	Date	SMP TECHNOLOGY, INC.
0	Issued				WHS	6/1/06	
							USB Connector, 12 Position, Right Angle Thru Hole, 2 Locks
SCALE	MAT'L		FINISH				
TOL. DEC.	.X +/- 0.3	.XX +/-	.XXX +/-	ANGLE +/-	UNIT: mm	SERIES: U 0 0 1 - 1 2 0 0 - 2 0 X - Z	Pg: 1