



ELECTRICAL:

CURRENT RATING: 1.5A Max.
 CONTACT RESISTANCE: 30 mW Max.
 INSULATION RESISTANCE: 500 mW Min.
 DIELECTRIC WITHSTANDING VOLTAGE:
 1000 Vrms 60 Sec. Min.

MATERIAL:

HOUSING: PBT Polyester or High Temp. Plastic
 COLOR: Black
 SPRING WIRE: 0.35mm Thickness Phosphor Bronze
 Gold Plating Over Nickel

MECHANICAL:

DURABILITY: 500 Mating Cycles Min.
 OPERATING TEMPERATURE: -25°C to +90°C

HOW TO ORDER:

U A 0 0 - X 0 1 0 - 0 0 X - Z

INSULATION MATERIAL:
 0 - PBT
 1 - PA46 (RJ45); LCP (USB)

USB CONNECTOR:
 1 - 1 USB STANDARD PROFILE

RoHS
 COMPLIANT

SELECTIVE PLATING:

6 - Au FLASH CONTACT AREA
 7 - 10u" Au CONTACT AREA
 8 - 15u" Au CONTACT AREA
 9 - 30u" Au CONTACT AREA

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	07/01/13
A	B.S.	B.S.	S.M.	03/16/17

SMP TECHNOLOGY, INC.
 Combo Jack; RJ45 and (1) USB, Shielded, No LEDs, w/ EMI Tabs